

# ARC WELDING TOOLS & ACCESSORIES

## SHORTSTUB™ ELECTRODE HOLDERS

- Grip the electrode closer to the end
- Allows you to use 20% more of the electrode than with standard tong holders
- Manufactured from copper alloy for maximum conductivity and strength
- Fibreglass insulators are designed to withstand intense heat and impact
- Will not burn, break or carbon char
- Electrode capacity: 3/32" (2 mm) - 3/16" (5 mm)



Model No.	Amps	Description	Price /Each
NT629	400	Electrode Holder w/Neck Ring	
NT631	600	Electrode Holder w/Neck Ring	
NT630	400	Slimline – Bernard® Style Holder	
NT818	-	Replacement Head for 400 Amps Electrode Holder	
TTV098	-	Replacement Head for 600 Amps Electrode Holder	



## BERNARD® SHORTSTUB™ ELECTRODE HOLDERS

- Electrode can be used to within one inch of Shortstub™ head
- Built to last with a proven high impact, high heat separate head
- 2000-lb. gripping pressure
- Better visibility, greater hand-to-arc distance



Model No.	Mfg. No.	Amps	Electrode Capacity"	Price /Each
360-9001	405	400	1/16 - 1/4	



## CAM ACTION CABLE CONNECTORS

- One model fits cable sizes 4 through 4/0
- Manufactured from heavy wall precision machined brass alloy
- Cable is held securely by large dome screw
- Brass body assembly slides easily into unique heavy-duty neoprene insulator with no external screws to avoid shock hazards
- Cam locking connectors are compatible with most common brands



Model No.	Description	Price /Each
NT664	Male/Female Connector Set	
NT649	Male Half with Insulator	
NT650	Female Half with Insulator	



## EITHER-END CABLE CONNECTORS

- For use with 1/0 - 2/0 cable
- Unique "Either-End" design allows ends to interlock without the need for male/female connection points
- Brass body assembly slides into heavy-duty neoprene insulator



Model No.	Mfg. No.	Description	Price /Each
NP528	E-102M	Either-End Connector Set	



## LC-10 CABLE CONNECTORS

- Positive lock-tight action
- Metal parts are precision machined from heavy, specially shaped brass extrusion
- Cam action design of male half connector pulls the two halves tightly together
- Female brass connector is recessed to minimize accidental shorting
- Molded connector covers
- 250 Amps
- Cable capacity: 4 - 1/0



Model No.	Mfg. No.	Description	Price /Each
380-1610	05040	Complete Connector Set	
380-1620	05043	Male Half	
380-1615	05046	Female Half	



## ELECTRICAL PLUGS & RECEPTACLES

- For use with copper or aluminum wire
- **Plug** - Universal angle ground, 50 amps, 250 volts, male
- **Receptacle** - 50 amps, 250 volts



Model No.	Mfg. No.	Description	Price /Each
NP495	42	Plug	
NP496	1252	Receptacle	

