
ERGONOMIC MATTING

HOG HEAVEN®

- Solid textured nitrile rubber surface for better chemical and oil resistance, and superior slip resistance
- Welding safe
- Electrically conductive
- Closed cell nitrile/PVC cushion 100% nitrile border .
- will not crack or curl
- Unmatched durability
- Available in black and . black/yellow safety stripes





5/8" THICK

Model	Dim.			Price
No.				/Each
BLACK NO. 4	21			
SAM152	2	х	3	
SAM153	3	х	5	
SAM154	3	х	12	
SAM155	4	х	6	
BLACK/YELL	OWN	10.4	23	
SAM159	2	х	3	
SAM160	3	х	5	
SAM161	3	х	12	
SAM162	4	х	6	

7/8" THICK

Model	Dim.			Price
No.				/Each
BLACK NO.	422			
SAM166	2	х	3	
SAM167	3	х	5	
SAM168	3	х	12	
SAM169	4	х	6	
BLACK/YEL	LOWN	10.4	24	
SAM173	2	х	3	
SAM174	3	х	5	
SAM175	3	х	12	
SAM176	4	х	6	

HAPPY FEET®

Combine exceptional

- anti-fatigue performance with unique safety features
- Dense closed-cell rubber cushion encapsulated with solid nitrile rubber Resistant to chemicals, animal
- fats and petroleum products Electrically conductive and safe
- for use in computer rooms and electrical parts manufacturing
- Safe for welding
- Low profile, beveled edges available with safety striped borders
- Colour: Black, black and yellow, other colours available on request





TEXTURE-SURFACE NO. 480

Model	Dim.			Price
				/Each
BLACK				
SAM180	2	х	3	
SAM181	3	Х	5	
BLACK/YELLOW				
SAM183	2	х	3	
SAM184	3	х	5	

CUSHION MAXTM

- · Superior anti-microbial, anti-fatigue mat for comfort and ergonomic benefits
- Made of 100% nitrile/PVC closed cell foam
- Diamond patterned surface that is more than twice as durable as traditional PVC foam mats
- Solid pattern helps to reduce slip and fall accidents while beveled borders make for a safe transition from floor to mat
- Cost effective alternative to
- traditional PVC foam mats Ozone resistant
- Recommended for use in warehouses, • picking lines, assembly lines, work stations, check out stations, labs or other wet or dry environments
- 5/8" thick
- Colour: Black .



Model	Dim.			Price	
No.				/Each	
SAR819	2	Х	3		
SAR820	3	х	5		
SAR821	3	х	12		
SAR822	4	х	6		

NON-CONDUCTIVE CORRUGATED SWITCHBOARD NO. 702 & DIAMOND PLATE SWITCHBOARD NO. 701

- Recommended usage: up to 17000 V
- The corrugated surface is abrasion resistant and easily cleaned

- Passes MSHA IC-246 fire
- resistance test (mining safety)

1-YEAR WARRANTY

WEARWELL


NO. 702 CORRUGATED SAL242 2 x 75 NB657 3 75 Х

NO. 701 DIAMOND-PLATE 2 x 75

Note: Other lengths available

Available with drainage holes

CAN INSULATE UP TO 30 000 V! High-performance non-conductive matting protects personnel in areas with dangerous high-voltage equipment Maximum rating: 30 000 V



1/4" thick



D-178-01 Type 2, Class II





SAL236

SAL238 3 75 Х