# **CAPACITANCE, PHASE & EARTH GROUND TEST**

# TESTERS



# CLAMP GROUND RESISTANCE TESTER

- Auto-ranging ground resistance and leakage current measurements
- 0.001  $\Omega$  resolution for low resistance measurements
- · 9999-count backlit LCD display
- Internal memory stores up to 99 readings
- User-adjustable alarms
- Data hold function
- · Durable double-molded conductor clamp
- 1.26" (32mm) jaw size for large ground rods
- Low battery indicator and auto shut-off after 5 minutes
- · Cat. III 300V safety rating
- Widely used to test the ground resistance of lightning arrestors, electrical distribution equipment, telecommunication systems, oil field equipment and gas station installations
- Includes: R5700 Ground Resistance Tester, 2 Resistance Calibration Loops (1  $\Omega$  and 10  $\Omega$ ), Batteries and Hard Carrying Case
- Power Supply: 4 AA Batteries





Model No.	Mfg. No.	Description	Price/Each
IB901	R5700	Resistance Tester	
IB902	R5700-NIST	Resistance Tester w/ISO Certificate	

### NON-CONTACT PHASE ROTATION TESTER

- Non-contact voltage sensing alligator clips promote safety
- LEDs indicate phase orientation (clockwise or counter-clockwise) and whether each phase is live
- Adjustable LED brightness allows for measurement in sunlight and lowly lit environments
- Beeper sounds intermittently when detecting correct phase and continuously for a reversed phase
- Durable housing with magnets frees hands and allows for easy measurement
- · Low battery indicator
- Includes: Rotation tester, 3 x color coded cables with alligator clips, battery and soft carrying case
- No. of Phases: 3
- Voltage Range: 75 to 1000VAC
- Overvoltage Category: CAT. III 1000V, CAT. IV 600V



# REED

Model No.	Mfg. No.	Description	Price/Each
IB943	R5044	Non-Contact Phase Rotation Tester	
IC559	R5044-NIST	Non-Contact Phase Rotation Tester w/ISO Certificate	

# Can't find what you're looking for? Call us today!

### LCR/CAPACITANCE METERS

- Measure inductance/capacitance/resistance with secondary parameters including dissipation factor (D), quality factor (Q), phase angle (Ø), equivalent series/parallel resistance (ESR or Rp)
- Autoranging operation for AC impedance and DE resistance measurement
- Auto I CR smart check and measurement
- Series/Parallel modes
- · Ls/Lp/Cp with D/Q/Ø/ESR parameters
- Support DCR mode 200 to  $200M\Omega$
- High accuracy with 4 or 5 terminal Kelvin measurement
- Testing frequency is up to 10kHz and output frequency is up to 100kHz
- Includes test leads and batteries
- · Accredited calibration available



### **SPECIFICATIONS:**

Inductance Range: 2000.0 μH/20.000/200.0/2000.0 mH/20.000/200.00/2000.0 H Capacitance Range: 2000.0 pF/20.000/200.00/2000.0 nF/20.00/200.00/2000 μF Resistance Range: 20.000/200.00 Ω/2.0000/20.000/20.000 kΩ/2.0000/20.000/20.00 MΩ Test Frequencies: 100/120/1k/10k/100k Hz

Model No.	Mfg. No.	Description	Price/Each
IA854	R5001	LCR/Capacitance Meter	
NJW155	R5001-NIST	LCR/Capacitance Meter w/ISO Certificate	

### **VOLTAGE/CURRENT DATA LOGGERS**

- Simultaneously measure 2 True RMS AC voltage inputs OR 2 AC current inputs OR 1 AC voltage and 1 AC current input
- · User programmable sample rates from 1 second to 24 hours
- Stores up to 256,000 measurements
- User programmable high/low alarms
- LCD indicates time/date, current readings, Max/Min, Peak hold and whether alarm settings have been exceeded
- Download collected data through USB interface
- · Auto power off and battery check
- Includes AC current clamp sensor and voltage sensor, USB cable, software, and battery
- Accredited calibration available

### SPECIFICATIONS:

AC Current Range: 10 to 200A AC Voltage Range: 10 to 600V



## REED

Model No.	Mfg. No.	Description	Price/Each
IA856	R5003	AC Voltage/Current Data Logger	
NJW157	R5003-NIST	AC Voltage/Current Data Logger w/ISO Certificate	

### PHASE SEQUENCE TESTERS

- Tests phase orientation of 3-phase power sources
- Indicates phase orientation (clockwise or counter-clockwise) and whether each of the three phases is live
- Also indicates direction of motor rotation
- · Determines motor rotation without contact
- Easy to open alligator clips with wide jaws
- Double molded housing
- Cat. III 600V safety rating
- Input Voltage: 40 to 600 VAC
- Operating Frequency: 2 to 400 Hz
   Complete with cables with 3 colour-coded
- Complete with cables with 3 colour-coded alligator clips, 9V battery and carrying case
   Accredited calibration available





		** **	
Model No.	Mfg. No.	Description	Price/Ea
IA857	R5004	Phase Sequence/Motor Rotation Tester	
NJW158	R5004-NIST	Phase Sequence/Motor Rotation Tester w/ISO Certificate	